


Electical Information	
Model No.	MBL-BLIPA6-22-TC-BLK
Power Consumption (±5%)	6 - 22Watt Power Adjustable (6.6W / 11W / 16.5W / 22W)
Power Supply	Done
Power Factor	>0.90
Surge Protection	1kV line-line, 2kV line-earth
Driver Type	Constant Current
Control	Dali
	Non Dimmable


Optic Information	
LED Type	SMD 3030
Luminous Flux (±10%)	1,920lm
Efficacy (5000K Ra70)	80lm/w
Tri - Colour Temp	3000K & 4000K
Colour Rendering Index	>70
Beam Angle	R03201, (Optional R03202, R03203)
UGR Level	N/A

Dimensions and Mount	
Dimensions	165 x 900mm (6.2kg)
Mounting Option	Mounting Kit with Anchor Bolts
Material	Aluminium Alloy & Polycarbonate Optical Lens
Finish	Powder Coating
Fixture Colour	Black
IK Rating	IK10
IP Rating	IP66

Lifespan and Warranty	
Operation Temperature	-30°C ~ +50°C
Life Time of LED @ Ta=25 °C	37,800 hrs-L90
	78,500 hrs-L80
Warranty	5 Year



Round House Side Shield  
To reduce glare



Mounting Kit with Anchor Bolts

Project Name	Type	Qty
Comments		